

## APPENDIX B SHELL SCRIPT EXAMPLES

The two files included here may be used as examples for creating the **.cshrc** and **.login** shell scripts.

```
# @(#)Cshrc 1.6 91/09/05 SMI
#####
#
#   .cshrc file
#
#####
#   set up search path
setenv USR_MOTIF_DIR /dsrscm/usr_motif
setenv UIDPATH ./%U:$USR_MOTIF_DIR/bin/sun_solaris/%U
# add directories for local commands
set lpath = (/opt/ICS/Motif/usr)

set path = (. ~ $lpath ~/bin /usr/local /usr/ucb /usr/bin /usr/etc /etc)
set path = ($path /usr/openwin/bin /usr/local/bin)

setenv ORACLE_HOME /usr/oracle
set path = ($PATH /$ORACLE_HOME/bin)
setenv ORACLE_SID dsrsdb

#   Set DSRS variables

source /dsrscm/command/setup.csh

#   aliases for all shells

alias cd      'cd \!*;echo $cwd'
alias cp      'cp -i'
alias mv      'mv -i'
alias rm      'rm -i'
alias pwd     'echo $cwd'
alias del     'rm -i'

#   settings for interactive shells

set history=40
set ignoreeof
set notify
set savehist=40
set prompt=""hostname': 'whoami':\!:"
```

```

# @(#)Login 1.14 90/11/01 SMI
#####
#
#
#   .login file
#
#   Read in after the .cshrc file when you log in.
#   Not read in for subsequent shells. For setting up
#   terminal and global environment characteristics.
#
#####
#   Leave lines for all but your remote terminal commented
#   out

if ($TERM != "sun") then
endif

#   Set Oracle environment variables, etc.

set ORAENV_ASK=NO
source $ORACLE_HOME/bin/coraenv
unset ORAENV_ASK
setenv OPENWINHOME /usr/openwin
setenv MOTIFHOME /opt/ICS/Motif/usr

#
# If possible, start the windows system. Give user a chance to bail out
#

    echo -n "Starting OpenWindows (type Control-C to interrupt)"
    sleep 2
    $OPENWINHOME/bin/openwin
    clear      # get rid of annoying cursor rectangle
    echo -n "Automatically logging out (type Control-C to
interrupt)"
    sleep 2
    logout    # logout after leaving windows system
    breaksw

```